Item	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
	SECTION :A				
	EARTHWORKS: Provisional				
	SUPPLEMENTARY PREAMBLES				
	Excavation to be done to fit the registered Engineers foundation desgin and specification.				
1	Site clearance Digging up and removing rubbish, debris, vegetation, hedges, shrubs, bush etc and trees including compaction and carting away excavated materials	ltem	3		
	Excavation in earth not exceeding 2m deep including compacting excvated surfaces				
2	Excavation in soft packable material	m <sup>3</sup>	13,5		
	Extra over trench and hole excavations in earth for excavation				
3	Medium-hard packable material	$m^3$	13,5		
4	Hard ground	$m^3$	13,5		
5	Extra over all excavateds for carting away Surplus material for excavations and/or stock pille on site, to a dumping site to be located by the contractor	m <sup>3</sup>	40,5		
	200mm thick G5 material compacted to 98% MOD  AASHTO density	3	4.0		
6	Under bases	m <sup>3</sup>	4,2		
	Total carried to summary				
	SECTION B: EARTHWORKS				

Item	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
	CONCRETE, FORMWORK & REINFORCEMENT				
	SUPPLEMENTARY PREAMBLES  Cost of tests				
	I ne cost of making, storing and testing of concrete cubes as required under clause 7 "tests" of SABS 1200 G shall include the cost of providing cube moulds necessary for the purpose, for testing costs and for submitting reports to the Architect. The testing shall be undertaken by an independent firm or institution nominated by the contractor to the approval of the architect				
	<u>Formwork</u>				
	Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"				
	30 Mpa Reinforced concrete cast against excavated				
1	surfaces 800mm Bases complete with holding down bolts for the tower structure	m <sup>3</sup>	21,6		
2	Test cubes  Making and testing 150 x 150 x 150mm concrete strength	No	3		
	Steel reinforcement to concrete work				
3	Reinforcement for base as per design	Tons	2,4		
	Formwork to sides				
4	Formwork to bases	m2	28,8		
5	50mm Blinidng	m <sup>3</sup>	1,8		
6	50mm Grout	m <sup>3</sup>	1,8		
	Total carried to summary				
	CONCRETE, FORMWORK & REINFORCEMENT				

Item	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1 2 3	ELEVATED WATER TANKS  Supply, deliver and install elevated 3660 x 2440 x 2440 mm (20 kl) Domestic Water Storage Tank (complete with covers, ball float valves level indicators, overflows, inlets, outlets and Ø65 drain connections as scheduled and specified) together with a steel structure 10m high to support the tank complete with ladders, balustrades etc. Allow for a 65mm diameter bore for drain and over-flow facility, 50mm diameter bore for water inlet facility and 75mm diameter for water outlet facility. Supply and fit pressure control valve at the base of the stand on the delivery main. Install SANS approved air release valve. Install 75mm Scour valves together with valve chambers. Install gate valve 75mm together with valve chamber. Install ball pressure valve 75mm together with valve chamber. Install pipe markers and Valve chamber markers. As per manufacturer details.  75mm Nominal bore (Tank Water Outlet Pipe) Supply and Install Galvanized (GSM) Pipework c/w fittings and supports (Provisional Quantity)  Water meter	No No	3 150 3	RATE	AMOUNT
	Total carried to summary  ELEVATED TANKS	<u>4</u>			

Item	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
	EXTERNAL WORKS				
1	Excavatepipe trench nominal depth of up to 1m depth	m	300		
2	Extra over for excavations in intermediate material  Extra over for excavations in hard rock material	m³ m³	90 90		
4	Lay 75mm uPVC class 9 (lay pressure test, bed and		300		
	backfill)	m			
5 6	Painting Work <b>Earthing</b> : Earthing to tank stand by a specialist supplier.  A soil resistivity test is to be done.	Item Item	3		
7	PADLOCK: Supply one HA1 padlock c. w. keys for cat ladder trap and a water meter sleeve.	No	6		
	and a water meter sleeve.				
	Total carried to summary				
	Total Carrieu to Summid y				
	EXTERNAL WORKS				
		<u>5</u>			
I	I			1	li I

Item	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
	PROVISIONAL SUMS				
1	Geotechnical Test Allow for a Geotechnical specialist to test ground samples and produce a Geotech report which will allow the Professional Structural/Civil Design engineer to do foundation design	Item	3		R 60 000,00
2	Allow for a registered engineer to design all work pertaining to the tank stand foundations and slab, supply of design certificate, engineering drawing, foundation construction certification and supervision of construction and certifying of foundation	Item	3		R 90 000,00
	Total carried to summary				R 150 000,00
	PROVISIONAL SUMS	<u>6</u>			
		<u> </u>			

2 3.100	SUMMARY PAGE		
Item			AMOUNT
1	PRELIMINARY AND GENERAL		
2	EARTHWORKS		
3	CONCRETE, FORMWORK & REINFORCEMENT		
4	ELEVATED WATER TANKS		
5	EXTERNAL WORKS		
6	PROVISIONAL SUMS		R 150 000,00
	Sub-total		
	Add 15% VAT		
	Carried to form of tender		
İ			